



MEDIUM BAY METAL HALIDE LUMINAIRE

METAL HALIDE FIXTURE WITH INTEGRAL HIGH POWER FACTOR BALLAST WITH OPTICAL CONTROL PRISMATIC GLASS REFLECTOR WITH SELF INDUCED CHIMNEY CLEANING ACTION. PROVIDE WITH MINIMUM COEFFICIENT OF UTILIZATION USING ZONAL CAVITY METHOD OF FLOOR 20%, CEILING 50%, WALL 50%, RCR OF 4, CU. = 0.68 MINIMUM. VOLTAGE AS SHOWN ON DRAWINGS.

FURNISH WITH 250W TUNGSTEN HALOGEN EMERGENCY TRANSFER SYSTEM TO TRANSFER LIGHT SOURCE FROM MAIN LAMP TO AUXILIARY LAMP DURING MOMENTARY POWER OUTAGES. LAMP TO RETRANSFER WHEN METAL HALIDE LAMP IS REIGNITED. FURNISH WITH RIGID CONDUIT SWIVEL HANGERS.

LAMP  
BALLAST

1 CLEAR METAL HALIDE  
BT-37 400W LAMP  
PEAK LEAD AUTO TRANSFORMER

MH-1  
12-2-88