

## Single Faller and Faller Modules INSPECTION FORM

Check configuration being dispatched	Module being dispatched for incident
	Type 1 Professional Single Faller
	Type 1 Professional Faller Module (2 Fallers)
	Type 2 Single Class C Certified Faller
	Type 2 Class C Certified Faller Module (2 Fallers)

### CHAINSAW(s)

Equipment	Description	Check
Chainsaws, 2 per faller	Operational	
	Minimum of 30" or longer bar	
	Power head minimum 67 cubic centimeter or larger	
	Operational spark arrester	
	Chainbrake (functional)	
	Maintenance tools, supplies, and parts to keep the saw operating in a safe and efficient manner (i.e. srench, files, chain, gas/oil)	
Chainsaw Serial number		
Chainsaw Serial number		

### OTHER EQUIPMENT

Equipment	Description	Check
Other Equipment	Wedges	
	Falling axe	
	Fire extinguisher, multi-purpose 5BC in the vehicle, accessible by operator. Current annual inspection tag and annual maintenance tag in regards to a 6 year annual inspection and every 12 years regarding a hydro test on all dry powder, metal fire extinguishers	

### VEHICLE(s)

Dependable ground transportation that meets all State and Federal law relating to motor vehicle operation.

Equipment	Description	Check
Ground Transportation	Must be 4-wheel or all wheel drive capable	
	Seatbelts available for all passengers	
	Capable of carrying saws and hazardous materials (i.e. fuel) external from the passenger compartment	
	Tires shall have load ratings in accordance with vehicle GVWR.	
	Tires (including spare) sound sidewalls, body and tire tread depth of a minimum of 6/32 or rear tires and 6/32 for steering axle tires.	
	All wheel drive vehicles shall have all season or mud and snow tire tread on all wheels	
	No prohibited marking (i.e. use of official agency shields or markings on private vehicles or property)	
Contractor is personally responsible for safe transport to and from the incident and while on the incident. OF-296 will be used for the saws and Transportation		

**PERSONAL PROTECTIVE EQUIPMENT (PPE)**

All PPE shall be in operable condition and shall be maintained in good repair throughout the duration of any assignment. All personnel shall be wearing PPE including boots, upon arrival at an incident. **PPE must be in good repair at the time of Inspection.**

Equipment	Description	Check
Boots	All leather, lace-up type, minimum 8 inches high with lug type sole in good condition (Steel toe boots are unacceptable)	
Hardhat	Plastic, Class B. ANSI Z89.1, 1986, OSHA approved, with chinstrap. Hardhat must also meet NFPA Standard 1977, 1998 Edition	
Gloves	One pair heavy-duty leather per person	
Chaps	One pair per person	
Eye Protection	One pair per person (meets standards ANSI 287, latest edition)	
Hearing Protection	Use hearing protection whenever sound levels exceed 85 dB	
Head Lamp	One lamp per person with batteries and attachment for hardhat.	
Fire Shelter	One serviceable shelter per person. National Fire protection Association (NFPA) Approved	
Flame Resistant Clothing	Minimum of (2) two full sets of flame resistant shirt and pants. For routine fireline duties, flame resistant clothing must: <ol style="list-style-type: none"> <li>1) Self-extinguish upon removal from heat source</li> <li>2) Act as effective thermal barrier by minimizing conductive heat transfer.</li> <li>3) Not melt or shrink to any appreciable degree upon decomposition during exposure to a high heat source</li> <li>4) Be manufactured from flame retardant treated (FRT) cotton, FRT rayon, FRT wool, aramid (Nomex), or other similar fabric</li> </ol>	

Proof of Workers compensation coverage for individual Faller(s)		
Vehicle insurance (cab card)		

Contractor's Signature		Date	
Inspector's Signature		Date	

**ADDITIONAL NOTES:**