

**TACTICAL WATER TENDER-- INCIDENT COMPLIANCE CHECKLIST**    *Date:* \_\_\_\_\_ *Time:* \_\_\_\_\_

*INCIDENT NAME:* \_\_\_\_\_ *INCIDENT NUMBER:* \_\_\_\_\_ *RESOURCE #:* E-\_\_\_\_\_

COMPANY/CONTRACTOR: \_\_\_\_\_

AGREEMENT NUMBER: \_\_\_\_\_

EQUIPMENT MAKE: \_\_\_\_\_ MODEL: \_\_\_\_\_

VIN/SERIAL #: \_\_\_\_\_

LICENSE PLATE, *State and #:* \_\_\_\_\_

OPERATOR NAME: \_\_\_\_\_

**EQUIPMENT and PERSONNEL REQUIREMENTS – TACTICAL WATER TENDER**

Type 1 2000+ gallons     Type 2 1000-1999 gallons

**Minimum Requirements**

*Not all inclusive; for additional clarification refer to agreement (SF-1449 section D)*

**Yes    No**

			Yes	No
1	<b>Equipment VIN/Serial # matches resource order</b> (Schedule of Items)	D.6.3.1		
2	<b>Check-In Process Completed</b>	D.6.5.3		
3	<b>OF-296 Vehicle/Heavy Equipment Pre-use Inspection Checklist completed</b>	D.17		
4	<b>Agreement</b> (One complete copy)	D.8		
5	<b>RT-130 Fire Line Refresher including Fire Shelter (current): Completed Date:</b>	D.3.1.1		
6	<b>Staffing / Personnel:</b> Minimum of 2 crew members. All crew members have valid and current qualification cards and government pictured I.D.	D.3.1.2 Exhibit N Exhibit O		
	FFT1 ( <i>Name</i> ): _____  FFT1 / FFT2 ( <i>Name</i> ): _____ <input type="checkbox"/> <i>Additional Personnel; see remarks</i>			
7	<b>Brakes on all axles</b>	D.2.1.2		
8	<b>All vehicles 36,000 GVWR or greater shall be installed with an operator-controlled auxiliary braking system in addition to the service brakes (i.e., engine retarder, transmission retarder, driveline retarder, or exhaust retarder)</b>	D.2.1.2		
9	<b>Company Name, Equipment I.D. # and DOT #: Affixed to both sides of truck cab</b>	D.2.2.3		
10	<b>Programmable Radios:</b> Minimum One Handheld. Also has two battery clamshells	D.2.3 Exhibit M		
11	<b>Fire Extinguisher:</b> 2A 10BC, securely mounted to the vehicle, accessible to the operator and with current annual inspection tag	D.2.1.2		

**Minimum Requirements – continued****Yes No**

			Yes	No
12	<b>Wheel Chocks:</b> 2 Each	Exhibit M		
13	<b>Audible reverse warning device (backup alarm)</b>	D.2.1.2		
14	<b>First Aid Kit,</b> 5 person minimum: 1 each	Exhibit M		
15	<b>Flashlight</b>	D.2.1.2		
16	<b>Line Gear (I.A. Gear / Day Pack):</b> Minimum of one per crew member	D.2.1.2		
17	<b>Boots:</b> All Leather 8” high with lug type sole in good condition	D.2.1.2		
18	<b>PPE:</b> <input type="checkbox"/> Hard Hat <input type="checkbox"/> Gloves <input type="checkbox"/> Eye Protection <input type="checkbox"/> Hearing Protection <input type="checkbox"/> Headlamp with batteries	D.2.1.2		
19	<b>Flame Resistant Clothing:</b> A minimum of two full sets of flame-resistant shirt and pants certified to NFPA 1977 standard.	D.2.1.2		
20	<b>Fire Shelter:</b> New generation	D.2.1.2		
21	<b>Tank:</b> shall be firmly attached to chassis frame or structurally sound flat bed	D.2.1.2		
22	<b>Tank Baffling:</b> <input type="checkbox"/> (1) longitudinal baffle regardless of width and one (1) transverse baffle. The distance between vertical tank walls and baffles, or between parallel baffles, shall not exceed 52”. <input type="checkbox"/> Free Floating Baffle System (Baffle Balls) <b>Note:</b> Vendor must have data sheets which validates that the baffling is sufficient to meet the manufacturers recommendation.	D.2.1.2		

**Minimum Inventory (Exhibit M)**

23	<b>Equipment Inventory: Permanently marked with vendor/company identification.</b> Markings should be etched or engraved, painting or marking with permanent markers is not acceptable, in addition the vendor is to maintain a complete inventory list.	D.2.1.2		
24	<b>1 - Live Hose reel 100’ non-collapsible with ¾-inch inside diameter</b>			
25	<b>1 - Nozzle, combination Fog/Straight Stream, 1½-inch NH female</b>			
26	<b>1 - Nozzle, Class A Foam, 1½-inch NH Female, min. 20 GPM at 100 PSI</b>			
27	<b>2 - Shovels</b>			
28	<b>2 - Pulaski’s</b>			
29	<b>1 - Spanner Wrench, combination 1 1/2 - inch to 2 1/2 - inch</b>			
30	<b>1 - Adjustable Hydrant wrench</b>			
31	<b>2 - Adapters, 1½-inch NH female to 1½-inch NPSH male</b>			
32	<b>2 - Adapters, 1½-inch NPSH female to 1½-inch NH male</b>			
33	<b>2 - Reducers, 2½-inch NH female to 1½-inch NH male</b>			
34	<b>1 - Reducer, 1½-inch NH female to 1-inch NPSH male</b>			
35	<b>1 - Double Male 1½-inch NH</b>			
36	<b>1 - Double Female 1½-inch NH</b>			
37	<b>1 - Gate Y 1½-inch NH</b>			
38	<b>1 - Fire Hose Clamp 2½-inch</b>			
39	<b>200’ 1½-inch cotton/synthetic hose NH thread</b>			
40	<b>50’ 2½-inch cotton/synthetic hose NH thread</b>			
41	<b>10 - Fusees (Fire starter)</b>			
42	<b>All Pumps shall have a discharge pressure gauge</b>	D.2.1.2		

**Minimum Inventory – continued**

**Yes No**

43	<b>Pump:</b> Pump Type: Auxiliary <input type="checkbox"/> or Power Take Off (PTO) <input type="checkbox"/>			
44	<b>20' Suction Hose, with strainer or screened foot valve</b>			
45	<b>Foam Proportioner System:</b>	D.2.1.2		
46	<b>Foam:</b> Minimum 5 gallons			
47	<b>Monitor:</b> Manual <input type="checkbox"/> Remote <input type="checkbox"/> None <input type="checkbox"/>			
48	<b>Spray Bar head(s) operational:</b> Spray Bar Configuration: Front <input type="checkbox"/> Rear <input type="checkbox"/> Both <input type="checkbox"/> Gravity <input type="checkbox"/> Pressure <input type="checkbox"/>	D.2.1.2 Exhibit J Exhibit M		
49	<b>1 - 2 ½ inch</b> Discharge outlet NH thread			
50	<b>2 - 1 ½ inch</b> Discharge outlet NH thread			
51	<b>4-inch Gravity Dump valve on rear of tank</b>	D.2.1.2		
52	<b>2½-inch Valve at bottom of tank with NH threads</b>			
53	<b>Full size spare tire:</b> With minimum of 4/32 tread and wheel securely mounted to the vehicle. The spare tire shall be easily accessible.	D.2.2.1.1		

***Optional Attributes***

54	<b>All-Wheel Drive</b>	D.6.2 Exhibit M		
----	------------------------	--------------------	--	--

Equipment meets agreement specifications       Equipment does not meet agreement specifications

Inspector: \_\_\_\_\_ Date: \_\_\_\_\_  
(Print and sign)

Contractor: \_\_\_\_\_ Date: \_\_\_\_\_  
(Print and sign)

Contractor given the opportunity to correct noted deficiencies (*See Remarks*)

Contactor successfully corrected noted deficiencies

Inspector: \_\_\_\_\_ Date: \_\_\_\_\_

**REMARKS:** \_\_\_\_\_

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_